


NO.	DESIGNATION	SIGNAL	DESCRIPTION
1	Type	TC	Magnetic Contactor
2	Model	11	12A
		16	16A
		21	24A
		30	30A
		35	35A
		40	44A
		50	58A
3	Auxiliary Contacts	60	68A
		none	1a1b
		A	1a
		B	1b
4	Coil Voltage (50Hz)	5	110VAC
		6	240VAC
		7	24VAC
		9	415VAC

**EXAMPLE**  
5.5kw 12A Contactor  
Normally open contacts  
240V



TYPE	AUXILIARY CONTACTS		AC1 RATED CURRENT	200/220V			380/440V			500/550V			RATED INSULATION
	N/O	N/C	Amps	A	Kw	Hp	A	Kw	Hp	A	Kw	Hp	V
TC11A TC11B	1 -	- 1	25 25	12	3	4	12	5.5	7.5	7	5.5	7.5	600
TC16A TC16B	1 -	- 1	30 30	16	4	5.5	16	7.5	10	10	7.5	10	600
TC21	1	1	40	24	5.5	7.5	21	11	15	17	11	15	600
TC30	1	1	50	30	7.5	10	27	15	20	22	15	20	600
TC35	1	1	60	35	9	12.5	33	18	25	27	18	25	600
TC40	1	1	65	44	11	15	40	22	30	32	22	30	600
TC50	2	2	80	58	15	20	52	30	40	41	30	40	600
TC60	2	2	100	68	19	25	65	37	50	52	37	50	600

